

ZU607TST

High brightness short throw laser projector



- **Bright short throw WUXGA laser projector - 6000 lumens**
- **30,000 hours maintenance-free laser light source at full brightness**
- **4K, HDR and HLG compatibility**
- **HDBaseT 3.0 connectivity**

At 6000 lumens, with 4K and HDR compatibility, the ZU607TST features a dust resistant IP6X certified optical engine for 24/7 operational capabilities and low maintenance. The ZU607TST short throw projector features extremely long-life laser technology, manual horizontal and vertical lens shift and built-in 15W speakers.



Specifications

UPC: 796435 44 675 8, EAN: 5055387667594, Colour: Black



Display/image	
Display technology	DLP
Resolution	WUXGA (1920x1200)
Brightness	6,000 lumens
Contrast ratio	300,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - horizontal	+/-15°
Keystone correction - vertical	+/-15°
Has vertical auto keystone correction	Yes
Displayable colors (millions)	1073.4
Horizontal scan rate	5~140HzKhz
Vertical scan rate	24~120HzHz
Uniformity	85%
Screen size	30" ~ 300" diagonal
Lamp info	
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	0.58:1
Projection distance	14.96" - 147.64"
Zoom type	Fixed
Focal length (mm)	8.51
Lens shift	Vertical -100 ~ 110%, Horizontal: +/-4%
Native offset	100%
Lens shift	Yes - see product downloads for more information
Connectivity	
Connections	Inputs 2 x HDMI 2.0, 2 x VGA, 1 x Composite video, 2 x Audio 3.5mm, 1 x USB-A power 1.5A Outputs 1 x HDMI 2.0, 1 x Audio 3.5mm, 1 x 3D sync, 1 x 12V trigger Control 1 x HDBaseT 4K, 1 x RJ45, 1 x RS232
LAN - wireless networking	No
General	
Noise level (min)	33dB
Noise level (max)	36dB
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
360° operation	Yes
Remote control	Backlit ProAV remote
Speaker count	2
Watts per speaker	15W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Networking	
LAN - control	Yes
LAN - wireless networking	No
LAN	Yes
Power	
Power supply	Universal AC 100--240V± 10%~ 50 / 60 Hz with PFC input
Power consumption (standby)	<0.5W
Power consumption (min)	240W
Power consumption (max)	366W
Weight and dimensions	
Dimensions (W x D x H)	14.72" x 11.89" x 4.61"
Gross weight	18.96 lbs
Net weight	13.89 lbs

